



export@sirsafety.com
www.sirsafety.com



UNI EN ISO 9001:2015
UNI EN ISO 14001:2015
UNI EN ISO 45001:2018

Name: High-eff respirator FFP2 NR D carbon w/v		Code: FA1327	FA13 RESPIRATORY PROTECTION - DISPOSABLE FFP2 MASKS
Description <p>High efficiency disposable respirator, specific for welding activities. Active carbon layer with exhalation valve. Appropriate for filtering acid vapours and fumes below the TLV. Suitable for medium toxic polluted environments, up to 12 times the TLV. Available in packs of 5 pieces.</p> <p>The product has been designed and manufactured to comply with Regulation (EU) 2016/425 and subsequent amendments.</p> <p>FFP2 NR D FFP2: Nominal Protection Factor: 12 Operational Protection Factor: 10 NR: disposable. D: The respirator haspassed the dolomite clogging test.</p>			
Category III	Colours	Available Sizes In stock: U	
Quantity/Carton 60	EC Standards EN 149 Class:FFP2 NR D		Important Information <p>Protects against solid and liquid aerosols in concentrations up to 12 times the TLV. Suitable for brush, water based and epoxy painting, sanding and grinding on paint, stucco and plastic, cleaning with solvents and water sprays, in chimneys and incinerators, agriculture, feed and tobacco processing, foundries, metal degreasing, galvanizing, welding and oxy-acetylene cutting.</p> <p>Make sure the product is in good condition and undamaged before use. Once you become aware of a damage, you should immediately replace it.</p> <p>Keep in a cool dry place, far from heat sources.</p>
Dexterity	Storage and cleaning		