SAFETY SYSTEM®
YOUR PROTECTOR

TECHNICAL SHEET

Sir Safety System S.p.A. Single-member company
Wholly-owned subsidiary of Sir Holding Srl
Via dei Fornaciai, 9 - Santa Maria degli Angeli
06081 Assisi - Perugia - Italy
Tel.+39 075.8043737 - Fax +39 075.8048686

VAT Nr. IT 03359340548
Viale Europa 74
20090 Cusago Milano
Tel. +39 02.90394575
Fax +39 02.90394441

export@sirsafety.com
www.sirsafety.com

UNI EN ISO 9001:2015
UNI EN ISO 14001:2015

Name: PREMIUM RESPIRATOR FFP2 NR D CARBON W/V	**Code: FA1328**	**FA13 RESPIRATORY PROTECTION - DISPOSABLE FFP2 MASKS**

Description

Premium respirator with activated carbon layer and exhalation valve.
Suitable for medium toxicity environments up to 12 times the TLV.
Available in packs of 10 pieces.

- Latex-free elastic, do not cause skin allergies.
- Better face adaptability, thanks to its concave shape.
- Completely metal-free to prevent rusting.
- Greater protection from fine and toxic dusts, due to its new filter surface which passed the D test. This test is performed with Dolomite dusts and certifies a higher level of protection with addedanti-clogging properties.
- Carbon layer: it prevents irritation caused by low concentration of gases and acid that can penetratetogether with dusts and aerosols.

The product has been designed and manufactured to comply with Regulation
(EU) 2016/425 and subsequent amendments.

FFP2 NR D
FFP2:
Nominal Protection Factor: 12
Operational Protection Factor: 10
NR: disposable.
D: Therespirator has passed the dolomite clogging test.

Category	Colours	Available Sizes
III		In stock: U

Quantity/Carton	EC Standards	Important Information
120	EN 149 Class:FFP2 NR D	Protects against solid and liquid aerosols in concentrations up to 12 times the TLV. Suitable for roller and epoxy painting, sanding and grinding on paint, cleaning and pest control in chimneys, agriculture, feed and tobacco processing, metal welding operations. Make sure the product is in good condition and undamaged before use. Once you become aware of a damage, you should immediately replace it. Keep in a cool dry place, far from heat sources.
Dexterity		Storage and cleaning