

Name: High-eff respirator FFP2NRD carbon w/v	Code: FA1330	FA13 RESPIRATORY PROTECTION - DISPOSABLE FFP2 MASKS
---	---------------------	--

Description

High-efficiency disposable respirator with activated carbon layer and exhalation valve. Specific for acid gases below the TLV level and in polluted environments with a medium level of toxicity up to 12 times the TLV.

Available in packs of 5 pieces.

- Outer PVC structure assures a constant ergonomic shape.
- Completely sealed edge with polyurethane guarantees insulation from the outside.
- Carbon layer: it prevents irritation caused by low concentration of gases and acid that can penetrate together with dusts and aerosols.
- Great filtering capacity due to the broad cup surface.
- Microfibre material with reduced breathing resistance.
- Fully adjustable wide head straps for precise fit conforming to the face.
- Completely metal free, to avoid rusting.
- Preformed moulded structure, conforming to any face shape.

The product has been designed and manufactured to comply with Regulation (EU) 2016/425 and subsequent amendments.

FFP2 NR D

FFP2:

Nominal Protection Factor: 12

Operational Protection Factor: 10

NR: disposable

D: The respirator has passed the dolomite clogging test.



Category III	Colours	Available Sizes In stock:
Quantity/Carton 200	EC Standards EN 149 Class: FFP2 NR D	Important Information Protects against solid and liquid aerosols in concentrations up to 12 times the TLV. Suitable for welding activities and in low concentration levels of smells and acids below TLV; brush, roller, water based and epoxy painting, cleaning and pest control on cement production, agriculture, feed and tobacco processing, metal degreasing, welding and oxy-acetylene cutting. Make sure the product is in good condition and undamaged before use. Once you become aware of a damage, you should immediately replace it. Keep in a cool dry place, far from heat sources.
Dexterity		Storage and cleaning