



Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 - Fax +39 075.8048686 VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 Fax +39 02.90394441 export@sirsafety.com www.sirsafety.com





Name: HIGH-EFF RESPIRATOR FFP3 NR D W/VALVE

Code: FA1412

FA14 RESPIRATORY PROTECTION - DISPOSABLE FFP3 MASKS

Description

High efficiency disposable respirator with exhalation valve. Suitable for use in highly toxic polluted environments up to 50 times the TLV. Available in packs of 5 pieces.

- Outer PVC structure gives a constant ergonomic shape.
- Completely sealed edge with polyurethane guarantees insulation from the outside.
- Carbon layer: it prevents irritation caused by low concentration of gases andacid that can penetrate together with dusts and aerosols.
- Great filtering capacity due to the broad cup surface.
- Microfibre material for reduced breathing resistance.
- Fully adjustable wide head straps for precise fit conforming to the face.
- Completelymetal free, to avoid rusting.
- Preformed moulded structure, conforming to any face shape.

The product has been designed and manufactured to comply with Regulation (EU) 2016/425 and subsequent amendments.

FFP3 NR D FFP3:

Nominal Protection Factor: 50 Operational Protection Factor: 30

NR: disposable

D: The respirator has passed the dolomite clogging test



Category	Colours	Available Sizes
III		U
Quantity/Carton	EC Standards	Important Information
	EN 149 Class:FFP3 NR D	Protects against aerosols and asbestos in concentrations up to 50 times the TLV. Suitable for grinding on fibreglass.
200		Make sure the product is in good condition and undamaged before use. Once you become aware of a damage, you should immediately replace it.
		Keep in a cool dry place, far from heat sources.
Dexterity		Storage and cleaning