

TECHNICAL SHEET

Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 - Fax +39 075.8048686 VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 Fax +39 02.90394441

export@sirsafety.com www.sirsafety.com





Description

Pre-moulded respirator with exhalation valve. Suitable for environments with high toxicity, up to 50 times the TLV.

Equipped withlatex free head straps and an internal foam layer to ensure sealing effect around the nose.

Available in packs of 20 pieces.

The product has been designed and manufactured to comply with Regulation

(EU) 2016/425 and subsequent amendments.

FFP3 NR FFP3:

Operational Protec NR: disposable Category	Colours	Available Sizes In stock: U
Quantity/Carton 200 Dexterity	EC Standards EN 149 Class:FFP3 NR	Important Information Protects against contaminants with high toxicity up to 50 times the TLV, such as asbestos, lead, chromium, nickel, uranium and other toxic elements. Suitable for sanding and grinding on fibreglass, demolition and cutting of asbestos, tunnel excavations. Make sure the product is in good condition and undamaged before use. Once you become aware of a damage, you should immediately replace it. Disposable equipment. Keep in a cool dry place, far from heat sources. Storage and cleaning