


| | | |
|--|---------------------|---|
| Name: 8 Fs ; 9 F`GAC?9`G5 J9F`7 : %`VfYUH` APPARATU | Code: FA2014 | FA20 RESPIRATORY PROTECTION ESCAPE SYSTEMS |
|--|---------------------|---|

Description

The Smoke Saver CF 15 constant flow emergency escape breathing apparatus (supplied with 3 litre 200 bar cylinder) is designed for escape from confined spaces in the event of an emergency, assuring autonomy of 15 minutes. The unit is activated automatically when the carrying bag is opened and the air flow cannot be interrupted until the cylinder is empty. The pressure regulator has a gauge and a clearly audible acoustic signal will sound when the residual air pressure in the cylinder is 50 bar. The Smoke Saver CF 15 is contained in an instantly recognizable high visibility orange carrying bag, easy to carry and in fire resistant material; inside the bag there is a fire-resistant hood fitted with a nose-mouth mask and a clear visor. Total weight 5.2 kg.

The product has been designed and manufactured to comply with Regulation (EU) 2016/425 and subsequent amendments.



| | | |
|--|---|---|
| Category III | Colours | Available Sizes Made to order: U In stock: |
| Quantity/Carton 1 | EC Standards EN 1146 CE Direttiva MED  SOLAS ISO 23269-1 | Important Information Escape from hazardous environments. |
| Dexterity | | Storage and cleaning |