

TECHNICAL SHEET

Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 - Fax +39 075.8048686 VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 Fax +39 02.90394441

export@sirsafety.com www.sirsafety.com





 Name: ONDA banded earplugs 15 pairs
 Code: FC1230
 FC12 EAR PROTECTION - REUSABLE EARPLUGS

 Description
 Polyurethane earplugs fitted on moulded headband. Avoids contact with
 Image: Code: FC1230

Polyurethane earplugs fitted on moulded headband. Avoids contact with work surface. Pack of 15 pairs. LATEX FREE

SRN 27 dB

Frequency in Hz: H Attenuation: 30 Frequency in Hz: M Attenuation: 24 Frequency in Hz: L Attenuation: 22 Freq.(Hz)/Mean Attenuation/Standard Dev./Value APV: 125/26.7/4.1/22.7; Freq.(Hz)/Mean Attenuation/Standard Dev./Value APV: 250/23.8/3.8/20.0; Freq.(Hz)/Mean Attenuation/Standard Dev./Value APV: 500/24.3/4.0/20.3; Freq.(Hz)/Mean Attenuation/Standard Dev./Value APV: 1000/26.4/3.8/22.6; Freq.(Hz)/Mean Attenuation/Standard Dev./Value APV: 2000/34.1/4.6/29.5; Freq.(Hz)/Mean Attenuation/Standard Dev./Value APV: 2000/34.1/4.6/29.5; Freq.(Hz)/Mean Attenuation/Standard Dev./Value APV: 4000/41.9/4.4/37.5; Freq.(Hz)/Mean Attenuation/Standard Dev./Value APV: 8000/44.3/4.3/40.0;



The product has been designed and manufactured to comply with Regulation (EU) 2016/425 and subsequent amendments.

Category	Colours	Available Sizes
III		In stock: U
Quantity/Carton	EC Standards	Important Information
	EN 352-2	Noisy working environments.
		Store in a cool, dry place away from heat sources. Before use, check that the earplugs are in perfect condition and replace them if they are not intact.
		The earplugs are disposalble and maintenance- free.
Dexterity		Storage and cleaning