

## HEARING PROTECTION INSERTS

### Spare earplugs for FC1230 (100 pairs)

#### FC1231

#### PERFORMANCE

SNR 27 dB

Frequency in Hz: H Attenuation: 30

Frequency in Hz: M Attenuation: 24

Frequency in Hz: L Attenuation: 22

Freq.(Hz)/Avg. Attenuation/Std. Dev./APV  
Value:125/26.7/4.1/22.7;

Freq.(Hz)/Avg. Attenuation/Std. Dev./APV  
Value:250/23.8/3.8/20.0;

Freq.(Hz)/Avg. Attenuation/Std. Dev./APV  
Value:500/24.3/4.0/20.3;

Freq.(Hz)/Avg. Attenuation/Std. Dev./APV  
Value:1000/26.4/3.8/22.6;

Freq.(Hz)/Avg. Attenuation/Std. Dev./APV  
Value:2000/34.1/4.6/29.5;

Freq.(Hz)/Avg. Attenuation/Std. Dev./APV  
Value:4000/41.9/4.4/37.5;

Freq.(Hz)/Avg. Attenuation/Std. Dev./APV  
Value:8000/44.3/4.3/40.0;



#### FIELDS OF USE

- > Agriculture - gardening - forestry
- > Food - cleaning - hospital
- > Construction - road works
- > Chemical-pharmaceutical industry
- > Light industry
- > Heavy industry
- > Logistics
- > Tertiary - trades

#### CERTIFICATIONS AND STANDARDS



**EN 352-2**

SNR: 27 dB

#### DETAILS

- Spare parts for polyurethane inserts on contoured headband;
- Pack of 100 pairs, bagged in pairs.

#### PACK

100 pairs

#### FEATURES

Replacement parts for polyurethane ear inserts on shaped headband (FC1230). Made of soft polyurethane, they ensure comfort and adaptability to the ear canal, ensuring effective noise reduction. The attenuation level makes them ideal for environments with moderate noise. The package includes 100 pairs, individually bagged in pairs. Latex free.

#### MAINTENANCE

Store in a cool, dry place and away from heat sources.  
The inserts are disposable and do not require maintenance.

#### QUANTITY PER CARTON

20

#### CATEGORY

III -> This product is currently planned and produced to comply with Regulation (EU) 2016/425 and subsequent modifications.

#### SIZES

##### ONE SIZE

- In stock
- On production
- Made to order
- Tailor made