

Name: SOKOI 3 SAFETY HARNESS	Code: FD1113	FD11 FALL ARREST DEVICES - HARNESSES
-------------------------------------	---------------------	---

Description

SOKOI 3 harness is made in polyester and it features:
ATTACHMENTS: 2 chest "A" attachments and 1 dorsal "D" attachment for the fall arrest system.

ADAPTABILITY: Adjustable shoulder straps and leg loops.

Sliding frontal plate for chest strap adjustment.

ADVANTAGES: Adjustable top and bottom.

ERGONOMICS: Integrated seat belt for increased worker's comfort.

MAXIMUM LOAD: 140 kg.

Sokoi harnesses are in polyester, which has a higher resistance to elongation than other materials. The harness does not stretch dangerously in the event of a fall, therefore, the worker does not risk slipping out of the harness.

Sokoi harnesses may be equipped, upon request, with a Tell-Tale fall indicator, positioned, through the seams, on the back of the shoulder; it detaches itself in the event of a fall. The harness must be immediately replaced after a fall.

Technical Specifications:

- Dorsal "D" Attachment for the fall arrest system.
- Shoulder attachment with adjustment.
- "A" or "A/2" label: indicate the attachment points of the fall arrest system.
- Labels: enclosed in a durable polyethylene bag to prevent the marking from fading.
- Sliders: the ends of the straps are locked by plastic clips.
- Chest strap fitted with single sliding buckle to allow the wearer to secure the strap in the desired position.
- Front attachments: All the textile loops are covered with a textile reinforcement.

The product has been designed and manufactured to comply with Regulation (EU) 2016/425 and subsequent amendments.



Category III	Colours	Available Sizes U
Quantity/Carton 1	EC Standards EN 361	Important Information Suitable for work at height. Read carefully the user sheet included. Make sure the item is in good condition, undamaged before use. Once you become aware of a damage, you should immediately replace it. Keep in a dry place, far from heat sources.
Dexterity		Storage and cleaning