



SAFETY SYSTEM®
YOUR PROTECTOR

Sir Safety System S.p.A. Single-member company
Wholly-owned subsidiary of Sir Holding Srl
Via dei Fornaciaci, 9 - Santa Maria degli Angeli
06081 Assisi - Perugia - Italy
Tel.+39 075.8043737 - Fax +39 075.8048686

VAT Nr. IT 03359340548
Viale Europa 74
20090 Cusago Milano
Tel. +39 02.90394575
Fax +39 02.90394441

TECHNICAL SHEET

export@sirsafety.com
www.sirsafety.com



UNI EN ISO 9001:2015
UNI EN ISO 14001:2015

Name: SOKOI 4 SAFETY HARNESS	Code: FD1114	FD11 FALL ARREST DEVICES - HARNESSES
-------------------------------------	---------------------	---

Description

SOKOI 4 harness is made in polyester and it features:
ATTACHMENTS: 2 textile sternal attachments and 1 dorsal D attachment for the fall arrest system.
 2 lateral D-rings for work positioning.
ADAPTABILITY: adjustable shoulder straps, leg loops and waist belt.
ADVANTAGES: hooks and rings for attaching tools on the back. Totally adjustable harness.
ERGONOMICS: with integrated seat belt increased worker's comfort.
MAXIMUM LOAD: 136 kg.

Sokoi harnesses are in polyester, which has a higher resistance to elongation than other materials. The harness does not stretch dangerously in the event of a fall, therefore, the worker does not risk slipping out of the harness.

Sokoi harnesses may be equipped, upon request, with a Tell-Tale fall indicator, positioned, through the seams, on the back of the shoulder; it detaches itself in the event of a fall. The harness must be immediately replaced after a fall.

Technical Specifications:

- Dorsal "D" Attachment for the fall arrest system.
- Shoulder attachment with adjustment.
- "A" or "A/2" label: indicate the attachment points of the fall arrest system.
- Labels: enclosed in a durable polyethylene bag to prevent the marking from fading.
- Sliders: the ends of the straps are locked by plastic clips.
- Chest strap fitted with single sliding buckle to allow the wearer to secure the strap in the desired position.
- Front attachments: All the textile loops are covered with a textile reinforcement.
- Side "D" rings to attach positioning lanyards.
- Padded waistbelt: increased support and comfort.

The product has been designed and manufactured to comply with Regulation (EU) 2016/425 and subsequent amendments



Category III	Colours	Available Sizes U
Quantity/Carton 1	EC Standards EN 358 EN 361	Important Information Suitable for work at height. Read carefully the user sheet included. Make sure the item is in good condition, undamaged before use. Once you become aware of a damage, you should immediately replace it. Keep in a dry place, far from heat sources.
Dexterity		Storage and cleaning