

FALL ARREST

Twin stopper fall arrest device 2 m

FD1215

DETAILS

- Double retractable cable, increased safety and redundancy during use;
- Length 2 meters, excellent balance between freedom of movement and control;
- Impact force reduction below 15 kN; greater operator protection and less stress on the body;
- Usable up to 100 kg, compatible with most users;
- 25 mm polyester webbing, high resistance to tension, wear, and tears;
- Supplied with energy absorber and an extra FD1627 - STANDARD carabiner.
- Aluminum alloy structure, robust, lightweight, and corrosion-resistant;
- Ideal for vertical work, high reliability in high-risk environments.

APPLICATIONS

Vertical work in hazardous locations.
Permitted user weight up to 100 kg.

IMPACT FORCE

Reduces falls with forces below 15 kN.

LANYARD

25mm polyester webbing.

STRUCTURE

Aluminum alloy

FEATURES

Retractable fall arrest device with double cable designed to ensure a high level of safety during vertical work. Equipped with an operating length of 2 meters, it ensures freedom of movement and immediate intervention in case of loss of balance. It is approved for a maximum user weight of up to 100 kg and allows the impact force to be reduced below 15 kN, effectively limiting the impact on the operator's body in case of a fall. The 25 mm polyester webbing ensures high resistance to wear and tear and traction, while the aluminum alloy structure offers robustness, lightness, and durability over time, even in harsh working conditions.



SIZES

ONE SIZE

-  In stock
-  On production
-  Made to order
-  Tailor made

CERTIFICATIONS AND STANDARDS



RETRACTABLE DEVICES
EN 360

FIELDS OF USE

- > Construction - road works
- > Works at a height

MAINTENANCE

Store in a cool and dry place, away from heat sources and protected from light.

QUANTITY PER CARTON

1