TECHNICAL SHEET

FALL ARREST

MAXI EAGLE fall arrest device

FD1222

DETAILS

- 4.7 cm wide webbing, for greater stability, resistance, and safety during use;
- Maximum length of 2.50 m, allowing ample freedom of movement at height;
- Self-retracting lifeline with automatic recovery, for immediate intervention in case of a fall;
- Protective polymer casing, offering high resistance to impacts, wear, and external agents;
- Integrated energy absorber, for effective reduction of impact force;
- Carabiner included, for quick, secure, and compliant connection to fall protection systems;

* Reliable for work at height, designed for intensive professional use.

SAFETY SYSTEM®
YOUR PROTECTOR

CATEGORY

III -> This product is currently planned and produced to comply with Regulation (EU) 2016/425 and subsequent modifications.

QUANTITY PER CARTON

1

FEATURES

Retractable webbing fall arrest device with automatic retraction, designed to ensure maximum safety during work at height. It features a 4.7 cm wide webbing that provides high strength and stability, with a maximum length of 2.50 meters, ideal for allowing ample freedom of movement while maintaining constant operator control. The protective polymer casing shields the internal mechanism from impacts and wear, ensuring reliable long-term performance. The device is equipped with an energy absorber, essential for reducing impact force in case of a fall, and a carabiner for a quick and secure connection to the fall arrest system.

FIELDS OF USE

> Construction - road works

> Works at a height

MAINTENANCE

Store in a cool and dry place, away from heat sources and protected from light.

AVAILABLE COLOURS

SIZES

ONE SIZE

In stock
On production
Made to order
Tailor made