TECHNICAL SHEET

POSITIONING SYSTEMS

Stopper w/retrievable handle

FD122700

DETAILS

- 20-meter retractable cable, maximum freedom of movement even at great heights;
- Integrated recovery handle, rapid intervention in case of emergency or operator in difficulty;
- Impact force reduction below 12 kN, high protection with significant impact reduction;
- Usable up to 100 kg, compatible with most operators;
- Galvanized steel cable, extremely high mechanical strength and corrosion protection;
- Reinforced impact-resistant polymer casing, maximum protection of the internal mechanism;
- Automatic arrest system, immediate response in case of a fall;
- Ideal for vertical work and dangerous positions, total safety in critical contexts.

APPLICATIONS

Vertical work in hazardous locations. Permitted user weight up to 100 kg.

IMPACT FORCE

Reduces falls with force under 12 kN.

LANYARD

Galvanized steel.

STRUCTURE

Reinforced impact-resistant polymer

FEATURES

Retractable fall arrest device with 20 meters cable and recovery handle, designed to ensure maximum safety during vertical work and operations in dangerous positions. The great length of the cable allows ample freedom of movement even at great heights, while the integrated recovery handle enables rapid intervention for lifting or recovering the operator in case of emergency. The device is approved for users weighing up to 100 kg and ensures an impact force of less than 12 kN, offering a very high level of protection and a significant reduction of impact on the body in case of a fall. The cable is made of galvanized steel, which guarantees very high mechanical resistance and corrosion protection, while the reinforced impact-resistant polymer casing protects the internal mechanism from impacts, external agents, and wear, ensuring reliability and long life even in the most demanding work environments.

AVAILABLE COLOURS

SIZES

ONE SIZE	20

In stock
On production
Made to order
Tailor made

CERTIFICATIONS AND STANDARDS

EN

RETRACTABLE DEVICES

EN 360

EN

EN 1496

CATEGORY

III -> This product is currently planned and produced to comply with Regulation (EU) 2016/425 and subsequent modifications.

FIELDS OF USE

> CONSTRUCTION - ROAD WORKS

> WORKS AT A HEIGHT

MAINTENANCE

Store in a cool and dry place, away from heat sources and protected from light.

QUANTITY PER CARTON

1