



**SAFETY SYSTEM®**  
YOUR PROTECTOR

**Sir Safety System S.p.A. Single-member company**  
Wholly-owned subsidiary of Sir Holding Srl  
Via dei Fornaciai, 9 - Santa Maria degli Angeli  
06081 Assisi - Perugia - Italy  
Tel.+39 075.8043737 - Fax +39 075.8048686

VAT Nr. IT 03359340548  
Viale Europa 74  
20090 Cusago Milano  
Tel. +39 02.90394575  
Fax +39 02.90394441

**TECHNICAL SHEET**

**export@sirsafety.com**  
**www.sirsafety.com**



UNI EN ISO 9001:2015  
UNI EN ISO 14001:2015

<b>Name: WORK POSITIONING LANYARD</b>	<b>Code: FD1524</b>	<b>FD15 FALL ARREST DEVICES - WORK POSITIONING SYSTEMS</b>
---------------------------------------	---------------------	--

**Description**

Work-positioning lanyard, fitted with polyamide triple twisted rope, diameter 14 mm, 2 m long, with 2 Standard carabiners.

Greenwire in the rope to indicate the deterioration of the material.  
Minimum breaking strength: 25 kN.  
Static strength: 15 kN supported for 3 minutes.  
Weight: 1085 g.  
Lifetime of the device: 10 years from the manufacturing date.



The product has been designed and manufactured to comply with Regulation (EU) 2016/425 and subsequent amendments.

Category	Colours	Available Sizes U
Quantity/Carton  <b>10</b>	EC Standards EN 358	Important Information Ideal for vertical tasks in dangerous positions.  Read carefully the user sheet included. Make sure the item is in good condition, undamaged before use. Once you become aware of a damage, you should immediately replace it.  Keep in a dry place, far from heatsources.
Dexterity		Storage and cleaning