

|  |                     |  |
|--|---------------------|--|
| <b>Name: Mobile anchoring device kit</b> | <b>Code: FD1811</b> | <b>FD18 FALL ARREST DEVICES - MOBILE ANCHORING DEVICES</b> |
|--|---------------------|--|

## Description

Designed for easy installation and removal, the system is tensioned using the tensioner and can be fitted to any suitable anchorage point (from 2000 daN). The lifeline is designed for use by one person at a time. Maximum deflection in the event of a fall: 2.44 m. The complete kit includes:

- a comfortable and resistant bag with closure device;
- 30 mm polyester webbing carefully rolled up (maximum length 20 m);
- a spool cable tensioner;
- two fixed point anchor belts (1 m) with rings;
- two positioning lanyards item no. FD1575;
- two FD1137 fall arrest harnesses.

Using the anchor on two fixed points to a maximum distance of 20 m, the device allows the normal working operations, connecting the worker equipped with a safety harness, who freely slide along the webbing through a lanyard with carabiner.

The product has been designed and manufactured to comply with Regulation (EU) 2016/425 and subsequent amendments.



|                                 |  |   |
|---------------------------------|--|---|
| Category<br><b>III</b>          | Colours  | Available Sizes<br>In stock: U  |
| Quantity/Carton<br><br><b>1</b> | EC Standards<br>EN 354<br><br>EN 361<br><br>EN 795 | Important Information<br>Assemble and disassemble scaffolding, covering exteriors of buildings or in other places where railing is temporarily missing.<br><br>Read carefully the user sheet included. Make sure the item is in good condition, undamaged before use. Once you become aware of a damage, you should immediately replace it.<br><br>Keep in a cool dry place, far from heat sources. |
| Dexterity                       |  | Storage and cleaning  |