

Name: Webbing and anchorage slings	Code: FD1812	FD18 FALL ARREST DEVICES - MOBILE ANCHORING DEVICES
---	---------------------	--

Description

Horizontal anchorage device with polyester webbing, 35 mm wide. Adjustable length from 5 to 20 metres. Equipped with two webbing anchorage slings with rings for the anchorage points. Designed for easy installation and removal, the system is tensioned using the tensioner and can be attached to any suitable anchor point (from 2000 daN). The lifeline is designed for use by one person at a time. Maximum deflection in the event of a fall: 2.44 m.

The complete kit includes:

- a comfortable and resistant bag with closure device;
- a carefully rolled up 30 mm polyester strap (maximum length 20 m);
- a spool cable tensioner;
- two anchor belts to the fixed point (1 m) with rings.

The product has been designed and manufactured to comply with Regulation(EU) 2016/425 and subsequent amendments.



Category III	Colours	Available Sizes In stock: U
Quantity/Carton 1	EC Standards EN 795	Important Information Assemblind and disassembling scaffoldings, covering exteriors of buildings or in other places where railing is temporally missing. Read carefully the user sheet included. Make sure the item is in good condition, undamaged before use. Once you become aware of a damage, you should immediately replace it. Keep in a cool dry place, far from heat sources.
Dexterity		Storage and cleaning