

Name: Gas alert MICROCLIP XL 1 gas LEL	Code: FG110007	FG11 ELECTRICAL DEVICES GAS DETECTORS
---	-----------------------	--

Description

Gas Alert Microclip XL 1 Gas, it detects 1 gas (Fuels).
It features a protection level equivalent to IP68, with water- resistance up to 45 minutes at a depth of 1.2 m. Battery operating time up to 18 hour, single button operating. Reliable battery performance, Reflex i Å technology to ensure the reactivity of the sensor, compact, lightweight and easy to use, green IntelliFlash i Ålashing lightfor an immediate visual confirmation.
Two-years warranty.

It features:

- Functioning guaranteed for at least a 12 hour shift, down to -20°C
- Rechargeable lithium polymer long-lasting battery, tested to withstand extreme conditions,
- Ergonomic, lightweight and easy to wear,
- Gas concentration constantly displayed on LCD screen,
- Alarm lightbars with a wide viewing angle,
- The IP68 protection ensures maximum protection against dust and water: up to 45 minutes at a depth of 1.2 m,
- Simple operation, tamper-proof with a single button and intuitive LCD icons,
- IntelliFlash i Åight shows whether the detector has been subjected to impacttests and is working properly
- Full function self-test of sensor, battery status, circuit integrity and audio/visual alarms.

Dimensions: 11,3 x 6,0 x 3,2 cm;

Weight: 190 g

Temperature: from -20°C up to 50°C

Humidity: from 0 up to 95% RH (without moisture)

Acoustic (95dB), visual and vibrating alarm. Low, high, TWA, STEL and OL (Over Limit).

Battery operating time:18 hours; It recharges in less than 6 hours

User options:

Reliability beep; Set STEL interval; On/off sensor; Alarms with manual reset; Safe display; stealth mode; calibration block; Auto-zero at startup; Automatic O2 calibration at startup; Set bump test interval; Mandatory impact test to overcoming of expiring date.

IP68 Nominal values: up to 45 minutes at a depth of 1,2 m.

Certifications: Class I, Div.1, Group A, B, C, D

ATEX: II 1 G; Ex ia IIC T4 Ga; IECEx: Ex ia IIC T4 Ga

European Compliance; KTL



Category	Colours	Available Sizes
		Made to order: U In stock:
Quantity/Carton	EC Standards	Important Information

1

EN 60079-0

EN 60079-11

ATEX

Values: II 1G Ex da ia IIC T4 Ga

IECEX

Values: Ex da ia IIC T4 Ga

Dexterity

Suitable to detect the presence of Fuels.

Make sure the product is in good condition, undamaged and clean before use. Once you become aware of a damage, you should immediately replace it.

Keep in a cool dry place, far from heat sources.

Storage and cleaning