TECHNICAL SHEET

MULTIGAS DETECTORS

Gas alert MICROCLIP X3 2 gas LEL/O2

FG110029

DETAILS

- Ergonomic and easily wearable;
- Real-time gas concentrations displayed on LCD;
- Autotest function for checking sensor integrity, battery status, circuit integrity, and acoustic/visual alarms;
- IntelliFlash function: constant visual confirmation of detector operating conditions and efficiency via flashing green light;
- Single-button operation;
- Compatible with IntelliDox management system for bump test and calibration;
- Data logging and logging of the 10 most recent gas presence events;
- High degree of protection against dust and water IP68 (up to 45 minutes at a depth of 1.2 mt);
- Shock-resistant and water-resistant protective casing.

FEATURES

Gas Alert Microclip X3 2 gas detects 2 gases (Combustibles and Oxygen). 18-hour battery life, single-button operation. Reliable battery performance, Reflex™ Technology to ensure sensor responsiveness, compact, lightweight and easy to use, IntelliFlash™ flashing green light for immediate visual confirmation. Oxygen sensor that does not require replacement during the detector's lifespan. Instrument lifespan: 5 years Warranty 3 years. Dimensions 11,3 x 6,0 x 3,2 cm; Weight 179 g Temperature From -20 to +50 °C Humidity : from 0 to 95% RH (non-condensing) Alarms Visual, vibration, acoustic (95 dB) • Low, high, TWA, STEL, over limit (OL)

SIZES

ONE SIZE

In stock
On production
Made to order
Tailor made

FIELDS OF USE

> CONSTRUCTION - ROAD WORKS

> CHEMICAL-PHARMACEUTICAL INDUSTRY

> LIGHT INDUSTRY

> HEAVY INDUSTRY

> PETROCHEMICAL INDUSTRY

QUANTITY PER CARTON

1

CERTIFICATIONS AND STANDARDS

EN **EN 60079-0**

EN **EN 60079-11**

ATEX
Values: II 1G Ex da ia IIC T4 Ga

IECEX
Values: Ex da ia IIC T4 Ga