TECHNICAL SHEET

SINGLE GAS DETECTORS

Gas alert BW solo O2 wireless

FG110108

DETAILS

- Small and lightweight
- Easy maintenance
- Technology Wireless Bluetooth™ Low Energy (BLE)
- Function Interflash activatable
- Operation with a single button
- Display easy to read
- Compatible with management system IntelliDox
- Automatic data recording and recording of the 50 most recent events of gas presence

FEATURES

Single-gas detector with Series 1 sensors for O2 (OXYGEN). Ensures high accuracy, long lifespan, and a faster sensor response time for the most frequently detected gases. The single-gas detector is easy to maintain, does not require disassembly to replace sensors, batteries, and sensor filters. Sensor lifespan up to 5 years. 3-year warranty (battery excluded). Alarm types: visual, vibration, acoustic (95 dB. Low, High, TWA, STEL, non-compliance. Withstands temperatures from -40 °C to 60 °C. 3-year warranty (battery excluded). Dimensions: 7 x 6.65 x 2.4 cm Weight: 95 gr

SIZES

ONE SIZE

In stock
On production
Made to order
Tailor made

FIELDS OF USE

> CONSTRUCTION - ROAD WORKS

> CHEMICAL-PHARMACEUTICAL INDUSTRY

> LIGHT INDUSTRY

> HEAVY INDUSTRY

> PETROCHEMICAL INDUSTRY

QUANTITY PER CARTON

1

CERTIFICATIONS AND STANDARDS

ATEX

Values: II 1G Ex ia IIC T4 Ga, I M1 Ex ia I Ma

IECEX

Values: Ex ia IIC T4 Ga, Ex ia I Ma