

Name: Gas alert BW solo H2S wireless	Code: FG110110	FG11 ELECTRICAL DEVICES GAS DETECTORS
---	-----------------------	--

Description

Single gas detector with series 1 sensors for H2S.
Assures high accuracy, long duration and faster sensor response time for the most commonly detected gases.

Dimensions: 140 x 60 x 36 mm

Weight: 103 to 116 g, depending on the sensor installed.

Operating temperature: -20 to +50 °C

Operating humidity: 10 to 90% RH

Operating pressure: 1013 to 116 kPa

Operating voltage: 3.6 V (Li-Ion battery)
Operating current: 15 mA (typical)
Operating power: 0.54 W (typical)
Operating frequency: 433 MHz (typical)
Operating range: 100 m (typical)
Operating mode: Low, High, TWA, STEL, non-compliance.

The single-gas detector is easy to maintain, does not need to be disassembled to replace sensors, batteries and sensor filters.

Sensor life 5 years. Warranty 3 years.



Category	Colours	Available Sizes
		Made to order: U In stock:
Quantity/Carton	EC Standards	Important Information
1	ATEX Values: II 1G Ex ia IIC T4 Ga, I M1 Ex ia I Ma IECEX Values: Ex ia IIC T4 Ga, Ex ia I Ma	
Dexterity		Storage and cleaning