SAFETY SYSTEM®
YOUR PROTECTOR

TECHNICAL SHEET

Sir Safety System S.p.A. Single-member company
Wholly-owned subsidiary of Sir Holding Srl
Via dei Fornaciai, 9 - Santa Maria degli Angeli
06081 Assisi - Perugia - Italy
Tel.+39 075.8043737 - Fax +39 075.8048686

VAT Nr. IT 03359340548
Viale Europa 74
20090 Cusago Milano
Tel. +39 02.90394575
Fax +39 02.90394441

export@sirsafety.com
www.sirsafety.com

UNI EN ISO 9001:2015
UNI EN ISO 14001:2015

Name: GAS ALERT BW ULTRA 4 GAS O2-LEL-H2S-CO	**Code: FG110111**	**FG11 ELECTRICAL DEVICES - BW GAS DETECTORS**

Description

Specifically designed for sampling and monitoring in confined spaces, Honeywell BW Ultra boasts state-of-the-art sensors, better visibility of the gas readings and higher levels of comfort and connectivity. It assures conformity to all safety standards, also offers the option of selecting a fifth sensor from a list of gases. It is fitted with a series 1 sensor, able to provide rapid response,reliable performances and long service life even in the most challenging environments.
FEATURES AND ADVANTAGES:
Ł Extraordinary ease of use.
Ł One-button tamper-proof operation.
Ł Intuitive LCD icons for faster decision making.
Ł Easy maintenance and service.
Ł Increased visibility thanks to large, intuitive dot matrix display for clearer reading.
Ł Intelligent gas layout for clearer sensor readings.
Ł Confined space mode for faster decision making.
Ł IntelliFlashÊ and Reverse IntelliFlashÊ technologies for full compliance with the regulations in force.
Ł Honeycomb case for added robustness.
Ł Intelligent arrangement of protection points.
Ł Display with scratch protection.
Ł Compatibility with Honeywell's Connected Worker solution.
Ł Honeywell TouchConnectÊ technology for function activation.
Ł Supported by Honeywell Safety Suite software for reporting.
Ł Ergonomic design for ease of use.
Ł Lightweight yet durable design.
Ł Perfectly adaptable to the hand for easy operation of sampling.
Ł Ultra fast.
Ł Fast response sensor technology.
Ł Large display for faster decision making.
Ł Fast calibration and impact testing (bump-testing) thanks to the system IntelliDoX.
Ł Dimensions: 14.8 x 8.5 x 4 cm.
Ł Weight: 411 gr (pliers included).
Ł Alarm types: visual, vibration, acoustic (95 dB); Low, High, TWA, STEL, Out of scale (OL).

Certifications: Class I, Div. 1, Group A, B, C, D
Class I, Zone 0, Group IIC; II 1G Ex ia IIC T4 Ga

Category	Colours	Available Sizes
		U

Quantity/Carton	EC Standards	Important Information
1		
Dexterity		Storage and cleaning