TECHNICAL SHEET

HEAT-RESISTANT GLOVES

SILEX heat-resistant glove

MA1625K1

LENGTH
38 cm

GAUGE
18 G

THICKNESS
4 mm

MATERIALS
Nylon

LINING
Thermal insulation

COATING
Liquid silicone

SURFACE
Smooth

DEXTERITY
5

AVAILABLE COLOURS
◯ K1 - WHITE

SIZES

8	9	10	11

In stock
On production
Made to order
Tailor made

FIELDS OF USE
> FOOD - CLEANING - HOSPITAL
> CHEMICAL-PHARMACEUTICAL INDUSTRY
> LIGHT INDUSTRY
> HEAVY INDUSTRY
> PETROCHEMICAL INDUSTRY

MAINTENANCE
Store in a cool and dry place, away from heat sources and protected from light. Clean with a soft-bristled brush and NEVER with alcohol, solvents, gasoline, etc. Allow to dry outdoors and NEVER on a direct heat source.

QUANTITY PER CARTON
36

CATEGORY
III -> This product is currently planned and produced to comply with Regulation (EU) 2016/425 and subsequent modifications.

CERTIFICATIONS AND STANDARDS

MECHANICAL HAZARD
EN 388
Abrasion: 4
Cut: 4
Tear: 3
Puncture: 1
ISO Cutting: X

HEAT PROTECTION
EN 407
Limited flame spread: 4
Contact heat: 2
Convective heat: 4
Radiant heat: X
Small splashes of molten metal: X
Large quantities of molten metal: X

COLD PROTECTION
EN 511
Convective Cold Resistance: 1
Contact Cold Resistance: 1
Water Permeable - Water Resistant: 1

FOODSAFE

CHEMICAL RISK
EN ISO 374-1
Sodium hydroxide, 40%: K
Sulphuric Acid, 96%: L
Formaldehyde, 37%: T

BACTERIOLOGICAL HAZARD
EN ISO 374-5
Protection: VIRUS

GENERAL REQUIREMENTS
EN ISO 21420