TECHNICAL SHEET

SPECIAL PROTECTION GLOVES

ELECTRO glove class 00

MA1818E0

LENGTH
36 cm

THICKNESS
0.5 mm

MATERIALS
Natural latex. 2,500V insulation.

FEATURES
The protective glove for live working, classified as Class 00, offers insulation up to 2,500V, ensuring reliable protection during electrical operations. Tested at a proof voltage of 2.5 kV for 3 minutes and a withstand voltage of 5 kV, suitable for working on electrical installations with a nominal voltage up to 500V AC and 750V DC. Made from high-quality materials, the glove is supplied in a sealed polyethylene pouch, ensuring it remains protected and in optimal condition until use. The glove is resistant to oil, acid, nitrogen, and low temperatures, making it extremely versatile and suitable for a wide range of industrial applications.

AVAILABLE COLOURS
E0 - YELLOW

SIZES

8	9	10	11

In stock
On production
Made to order
Tailor made

FIELDS OF USE
> CONSTRUCTION - ROAD WORKS

> CHEMICAL-PHARMACEUTICAL INDUSTRY

> LIGHT INDUSTRY

> HEAVY INDUSTRY

> PETROCHEMICAL INDUSTRY

> WORKS AT A HEIGHT

> TERTIARY - TRADES

MAINTENANCE
Store in a cool and dry place, away from heat sources and protected from light. Clean with a soft-bristled brush and NEVER with alcohol, solvents, gasoline, etc. Allow to dry outdoors and NEVER on a direct heat source.

QUANTITY PER CARTON
1

CATEGORY
III -> This product is currently planned and produced to comply with Regulation (EU) 2016/425 and subsequent modifications.

CERTIFICATIONS AND STANDARDS
ELECTRICAL HAZARD

IEC 60903

Acid, Oil, Ozone: R

Resistant to very low temperatures: C