



SAFETY SYSTEM®
YOUR PROTECTOR

Sir Safety System S.p.A. Single-member company
Wholly-owned subsidiary of Sir Holding Srl
Via dei Fornaciai, 9 - Santa Maria degli Angeli
06081 Assisi - Perugia - Italy
Tel.+39 075.8043737 - Fax +39 075.8048686

VAT Nr. IT 03359340548
Viale Europa 74
20090 Cusago Milano
Tel. +39 02.90394575
Fax +39 02.90394441

TECHNICAL SHEET

export@sirsafety.com
www.sirsafety.com



UNI EN ISO 9001:2015
UNI EN ISO 14001:2015

Name: CAMARO BLACK SANDAL	Code: MB1815Z9	MB18 FOOTWEAR - TOTAL PLANE SERIES
----------------------------------	-----------------------	---

Description

Dissipative sandal with composite toecap and midsole, having a constant thickness of 4 mm. Air Mesh fabric upper and eco-friendly leather overcap. Metal Free. S1P.
REACTOR SOLE: (PU/TPU) The wide cell polyurethane sole assures a very high shape memory effect. The TPU outsole assures long life, extreme mechanical resistance, flexibility, softness and hydrocarbon resistance. It has been designed with continuous horizontal grooving that supports flexion and foot movements. SRC slip resistant.
 insole: Cross-foam insole madewith solid material in polyurethane foam with variable thickness: 2.5 mm at the front and 9 mm in the heel area. Lined and perforated in the plantar area with outstanding anti-shock properties. Antistatic.
 DRY-PLUS polyester lining offering superb absorbing properties prevents feet overheating.





Main features:

- The wide fit, the conformation of the flat sole with 100% adhesion to the ground and the softness that gives the polyurethane to wide cells, improve comfort, reduce fatigue and increase efficiency.
- The additional overcap protects the shoe from shocks.
- Recommended on smooth and uniform surfaces

The product has been designed and manufactured to comply with Regulation (EU) 2016/425 and subsequent amendments.

Category II	Colours BLACK	Available Sizes 35 - 44
-----------------------	-------------------------	-----------------------------------

Quantity/Carton 10	EC Standards EN ISO 20345  Safety Class:S1P SRC EN 61340 	Important Information Industrial plants, Construction and Road Work Sites, Logistics and Handling. Keep the footwear dry and clean in an appropriate environment at ambient temperature. The wet footwear should never be placed in direct contact with a heat source after use, but shallbe air-dried in a ventilated environment at ambient temperature. Make sure footwear is in good condition, before use. If the shoes are damaged, replace them. Clean the footwear with a soft brush and water. Do not use any substance such as alcohol, methyl ethyl ketone, thinners, gasoline, petrol or any other type of chemicals that could damage the materials, causing non-visible weakenings and compromise the original protective features.
	Dexterity	Storage and cleaning