TECHNICAL SHEET

TOTAL PLANE

PLATINUM shoe

MB1824Z9



UPPER
Extra strong Nubuck leather offers superior resistance to wear and external agents, ensuring greater durability of the footwear even in demanding working conditions.

CLOSING
Laces

LINING
3D-TEX Polyester, with high wicking power thanks to the absorptive capacity of its fabric and structure.

TOECAP
Composite, for high impact protection while keeping the footwear lighter and thermally insulated.

PUNCTURE-PROOF
Composite with a constant thickness of 4 mm, it guarantees uniform protection against perforations, while ensuring lightness and flexibility.

FOOTBED
Monolithic polyurethane foam material with variable thickness: 2.5 mm in the front part and 9 mm in the heel area. Lined and perforated in the sole area with significant anti-shock properties. Antistatic. Removable footbed.

SOLE
PU/TPU. The wide-cell polyurethane midsole allows for a high memory effect. The TPU outsole guarantees durability, mechanical resistance, flexibility, softness, and hydrocarbon resistance; it has been designed with continuous horizontal grooves that promote foot flexion and movement.

FEATURES
The wide fit, the flat sole configuration with 100% ground adhesion, and the softness provided by the large-cell polyurethane improve comfort, reduce fatigue, and increase efficiency. The toe cap protects the footwear from impacts.
Recommended for smooth and even surfaces.

AVAILABLE COLOURS
● Z9 - BLACK

SIZES
39 | 47

In stock
On production
Made to order
Tailor made

FIELDS OF USE
> CHEMICAL-PHARMACEUTICAL INDUSTRY
> LIGHT INDUSTRY
> WORKS AT A HEIGHT
> LOGISTICS
> TERTIARY - TRADES

MAINTENANCE
Store clean footwear in a cool, dry place, away from heat sources and away from light.
The shoes must be cleaned with a soft brush and water.
Do not use chemicals that could damage the materials.

QUANTITY PER CARTON
10

CATEGORY
II -> This product is currently planned and produced to comply with Regulation (EU) 2016/425 and subsequent modifications.

CERTIFICATIONS AND STANDARDS
SAFETY FOOTWEAR
EN ISO 20345
Values: S3 SRC

ESD DEVICES
EN IEC 61340-5-1