TECHNICAL SHEET

OVERCAP

OVERCAP MAX SAFETY shoe

MB2113Z9

UPPER
Oiled Crazy Horse leather, smooth to the touch, extremely resistant to wear and tear. The TPU toe cap offers extra protection for the leather from impacts and abrasions.

CLOSING
Eyelets with leather construction for greater durability

LINING
3D-TEX Polyester, with high wicking power thanks to the absorptive capacity of its fabric and structure.

TOECAP
Composite, for high impact protection while keeping the footwear lighter and thermally insulated.

PUNCTURE-PROOF
Composite, provides high protection against perforations while keeping the footwear light and flexible, improving comfort and freedom of movement.

FOOTBED
DUAL FRESH two-components with variable thickness and high anti-shock characteristics, prevent the sweating effect. Removable footbed.

SOLE
PU FORCE. Dual-density Polyurethane. High-density polyurethane tread. Anti-fatigue low-density polyurethane insole. Extra-large fit. SRC slip-resistant.

FEATURES
Metal Free High-efficiency breathable lining, leather eyelets for increased durability, special scuff cap protection, sharp-edged lugs for improved grip on wet floors, and increased sole height, oil and hydrocarbon resistant tread, shock absorption system, increased wide fit suitable for any foot type.

AVAILABLE COLOURS
● Z9 - BLACK



SIZES
39	46	47

In stock
On production
Made to order
Tailor made

FIELDS OF USE
> AGRICULTURE - GARDENING - FORESTRY
> CONSTRUCTION - ROAD WORKS
> LIGHT INDUSTRY
> PETROCHEMICAL INDUSTRY
> WORKS AT A HEIGHT
> LOGISTICS

MAINTENANCE
Store clean footwear in a cool, dry place, away from heat sources and away from light.
The shoes must be cleaned with a soft brush and water.
Do not use chemicals that could damage the materials.

QUANTITY PER CARTON
5

CATEGORY
II -> This product is currently planned and produced to comply with Regulation (EU) 2016/425 and subsequent modifications.

CERTIFICATIONS AND STANDARDS
EN ISO
SAFETY FOOTWEAR
EN ISO 20345
Values: S3 SRC