TECHNICAL SHEET

MAXIMUM

MAXIMUM OASIS shoe

MB2311Z9



UPPER
Microfiber offers high resistance to wear and external agents while maintaining lightness and flexibility, thus ensuring prolonged comfort and increased footwear durability.

CLOSING
Laces

LINING
Polyester, offers high wicking power thanks to the high absorbent capacity of its fabric and structure.

TOECAP
Fiberglass, lightweight, offers high protection against impacts and compressions, ensures good thermal insulation.

PUNCTURE-PROOF
Composite with a constant thickness of 4 mm, it guarantees uniform protection against perforations, while ensuring lightness and flexibility.

FOOTBED
Monolithic material made from the union of EVA and RUBBER with variable thickness: 5 mm in the front part and 10 mm in the heel area. Antistatic. Removable footbed.

SOLE
PU/RUBBER. The inner part is made of large-cell polyurethane with memory effect to increase cushioning and the anti-shock effect. The nitrile rubber tread, with its pronounced and two-tone black/red pattern, features resistance to hydrocarbons as well as slip resistance on wet surfaces. The red inserts, with higher density and hardness, provide the sole with anti-torsion characteristics and make it suitable for gravelly, rocky, or uneven environments.

AVAILABLE COLOURS
● Z9 - BLACK

SIZES

40	41	42	43	44
45	46	47		

In stock
On production
Made to order
Tailor made

FIELDS OF USE
> CONSTRUCTION - ROAD WORKS
> LIGHT INDUSTRY
> HEAVY INDUSTRY
> PETROCHEMICAL INDUSTRY
> WORKS AT A HEIGHT

MAINTENANCE
Store clean footwear in a cool, dry place, away from heat sources and away from light.
The shoes must be cleaned with a soft brush and water.
Do not use chemicals that could damage the materials.

QUANTITY PER CARTON
10

CATEGORY
II -> This product is currently planned and produced to comply with Regulation (EU) 2016/425 and subsequent modifications.

CERTIFICATIONS AND STANDARDS
EN ISO

SAFETY FOOTWEAR
EN ISO 20345
Values: S3S HI HRO FO SC SR