TECHNICAL SHEET

MAXIMUM

POLAR boot

MB2326Z9



UPPER
Full-grain leather, water-repellent suede ankle strap and tongue, ensures high resistance and superior protection against moisture and wear, while offering stable and lasting comfort during use.

CLOSING
FitGO quick lacing system

LINING
Polyester knit with WR PTFE membrane and 400-gram Thinsulate insulation, it provides excellent thermal insulation and effective moisture protection, keeping the foot warm and dry even in the coldest weather conditions.

TOECAP
Fiberglass, lightweight, offers high protection against impacts and compressions, ensures good thermal insulation.

PUNCTURE-PROOF
Composite with a constant thickness of 4 mm, it guarantees uniform protection against perforations, while ensuring lightness and flexibility.

FOOTBED
Monolithic material made from the union of EVA and RUBBER with variable thickness: 5 mm in the front part and 10 mm in the heel area. Antistatic. Removable footbed.

SOLE
PU/RUBBER. The large-cell polyurethane midsole provides excellent memory retention. The nitrile rubber outsole, with its pronounced, two-tone black/red tread pattern, offers resistance to hydrocarbons and slip resistance in wet conditions. The red inserts, with higher density and hardness, give the sole anti-torsion properties and make it suitable for gravelly, rocky, or uneven environments.

FEATURES
Very wide fit, ideal for environments with hydrocarbons and chemical substances, cushioned sole with anti-shock effect, High Durability Cap System: high-durability TPU toe cap, suitable for gravelly, rocky, or uneven environments.

AVAILABLE COLOURS
● Z9 - BLACK

SIZES

38	39	40	41	42
43	44	45	46	47

In stock
On production
Made to order
Tailor made

FIELDS OF USE
> CONSTRUCTION - ROAD WORKS
> LIGHT INDUSTRY
> HEAVY INDUSTRY
> PETROCHEMICAL INDUSTRY
> WORKS AT A HEIGHT

MAINTENANCE
Store clean footwear in a cool, dry place, away from heat sources and away from light.
The shoes must be cleaned with a soft brush and water.
Do not use chemicals that could damage the materials.

QUANTITY PER CARTON
5

CATEGORY
II -> This product is currently planned and produced to comply with Regulation (EU) 2016/425 and subsequent modifications.

CERTIFICATIONS AND STANDARDS
EN ISO

SAFETY FOOTWEAR
EN ISO 20345
Values: S3 WR CI HI HRO SRC