

SPECIAL PROTECTIONS

APOLLO 12 boot

MB2414ZE

UPPER

Full-grain leather, oiled, with Bycast reinforcement. Bycast is a type of leather that is treated with a polyurethane coating to improve its durability and appearance. This process gives the leather a glossy and resistant finish, making it easier to clean and maintain.

LINING

Lining in Tepor® waterproof membrane, an elastic material that ensures water protection while maintaining breathability.

TOECAP

Steel, offers high protection against impacts and compressions.

PUNCTURE-PROOF

Zero-penetration, non-magnetic, antistatic, and thermal insulating composite. It offers flexibility and protection throughout the sole of the foot.

FOOTBED

Fustatic antistatic anatomical, made with materials that reduce the accumulation of static electricity, preventing electric shocks and improving safety in work environments where this risk is present. Removable footbed.

SOLE

Nitrile rubber resistant to contact heat up to 300°C.


FEATURES

Antistatic boot for firefighters, suitable for firefighting and rescue operations. It offers cold insulation (CI) and heat insulation up to 250°C (HI3).

WEIGHT

990 g (size 42)

AVAILABLE COLOURS

 ZE - Black/red



SIZES

38	39	40	41	42
43	44	45	46	47
48				

	In stock
	On production
	Made to order
	Tailor made

FIELDS OF USE

- > Agriculture - gardening - forestry
- > Petrochemical industry

MAINTENANCE

Store clean footwear in a cool and dry place, away from heat sources and protected from light. Footwear must be cleaned with soft-bristled brushes and water. Do not use chemical substances that could damage the materials.

QUANTITY PER CARTON

10

CERTIFICATIONS AND STANDARDS



SAFETY FOOTWEAR
EN ISO 20345
Values: SB CI AN SRC



FOOTWEAR FOR FIREFIGHTERS
EN 15090
Values: F2A HI3