

TECHNICAL SHEET

BOOTS

UB40 boot

MB2522Z9

UPPER

PVC (polyvinyl chloride), a thermoplastic material offering good abrasion resistance and flexibility.

LINING

Polyester

TOECAP

Steel, offers high protection against impacts and compressions.

PUNCTURE-PROOF

Steel for effective protection against perforations.

FOOTBED

/

SOLE

PVC

FEATURES

Footwear resistant to animal fats, vegetable oils, hydrocarbons, and chemicals, ensuring safety even in the most demanding environments. The structure is designed to maintain exceptional softness and flexibility, even at low temperatures, ensuring freedom of movement and prolonged comfort. Non-slip.

WEIGHT

1100 g (size 42)

AVAILABLE COLOURS



E0 - Yellow



Z9 - Black

SIZES

36	37	38	39	40
41	42	43	44	45
46	47			

In stock
On production
Made to order
Tailor made



FIELDS OF USE

- > Agriculture - gardening - forestry
- > Construction - road works
- > Light industry
- > Heavy industry
- > Petrochemical industry
- > Tertiary - trades

MAINTENANCE

Store clean footwear in a cool and dry place, away from heat sources and protected from light.
Footwear must be cleaned with soft-bristled brushes and water.
Do not use chemical substances that could damage the materials.

QUANTITY PER CARTON

5

CATEGORY

II -> This product is currently planned and produced to comply with Regulation (EU) 2016/425 and subsequent modifications.

CERTIFICATIONS AND STANDARDS



SAFETY FOOTWEAR

EN ISO 20345

Values: S5 FO SR