

Sir Safety System S.p.A. Single-member company Wholly-owned subsidiary of Sir Holding Srl Via dei Fornaciai, 9 - Santa Maria degli Angeli 06081 Assisi - Perugia - Italy Tel.+39 075.8043737 - Fax +39 075.8048686

VAT Nr. IT 03359340548 Viale Europa 74 20090 Cusago Milano Tel. +39 02.90394575 Fax +39 02.90394441

export@sirsafety.com www.sirsafety.com





Name: POLYTECH COLOR JACKET Code: MC5734H5 MC57 CLOTHING - POLYTECH SERIES

Description

Jacket in 75% cotton, 24% polyester, 1% antistatic fibre fabric, weight 290 g/m. It features a Chinese collar with Velcro for neckprotection, concealed zipper closure with metal snap buttons, two lower pockets and two chest pockets with flaps and Velcro, elastic cuffs, military style epaulettes, reflective piping on the chest.

THE JACKET SHALL BE WORN IN COMBINATION WITH THE TROUSERS.

- The Polytech series is made with a multi-purpose fabric that combines antistatic properties with resistance to flames, heat and chemical products.
- Thanks to its features it is multi-purpose, practical and resistant, breathable and comfortable.

The producthas been designed and manufactured to comply with Regulation (EU) 2016/425.

In combination with the coverall, is it possible to wear our under garments: Carboflame undershirt art. MC5610 and Carboflame underpants art. MC5620.

V@Á, æāļÁn¢¢^¦}ædÁæà¦a&ÁáaÁUÒSUË/ÒÝíÁÚæa)åædåÁF∈€Á certified



Available Sizes

Important Information

Oil & Gas industry.

immediately replace it.

and direct light.

Petrochemical Industry, Metalworking Industry,

Refining Industry, Chemical Industry, Industrial

Maintenance and Assemblies, Gas, Water and Electricity Mains Maintenance and Management,

Keep in a cool dry place, far from heat sources

Make sure the garment is in good condition,

become aware of a damage, you should

avoid the transfer of inflammable fibres.

undamaged and clean before use. Once you

We recommend to follow the washing instructions. Wash separately from other types of garments to

38 - 70



Category

Ш

1

Colours

ORANGE

Quantity/Carton

EC Standards

EN 1149-5



EN ISO 11611



Class:1;A1;

EN ISO 11612



Limited Flame Spread:A1 Convective Heat:B1 Radiant Heat:C1 Molten Iron Splashes:E3 Contact Heat:F1

EN 13034



Type:6

CEI EN 61482-2



APC:1

Dexterity

Storage and cleaning









