

Name: Fr back METAL SPLASH jacket	Code: MC6114B0	MC61 CLOTHING - NEW METAL SPLASH SERIES
--	-----------------------	--

Description

Jacket in 54% **Wool**, 20% Polyamide, 5% Aramid, 1% Antistatic Fibre, weight 330 g/m and with Flame Retardant breathable rear protection. Concealed zipper closure with flap, Chinese collar with Velcro closure, elastic inner cuffs, four external pockets with flap and Velcro.

THE JACKET SHALL BE WORN IN COMBINATION WITH THE TROUSERS

- Protects during welding operations and aluminium splashes
- Its remarkable properties do not limit the softness and breathability




Suitable to protect the operator from short contacts with the flame, in presence of low values of convective and radiant heat, in welding operations and related processes and from small splashes of molten metal.

The product has been designed and manufactured to comply with Regulation (EU) 2016/425 and subsequent amendments.

Protection levels indicated refer to the combination jacket and trousers.

certified



Category III	Colours GREY	Available Sizes Made to order: 44 - 62 In stock:
Quantity/Carton 20	EC Standards EN 1149-5  EN ISO 11611  Class:1 Values:A1 EN ISO 11612  Limited Flame Spread:A1 Convective Heat:B1 Radiant Heat:C1 Molten Iron Splashes:E2 Contact Heat:F1	Important Information Aluminium Industry, Foundries, Cement Industry. Keep in a cool dry place, far from heat sources and direct light. Make sure the garment is in good condition, undamaged and clean before use. Once you become aware of a damage, you should immediately replace it. We recommend to follow the washing instructions.
Dexterity		Storage and cleaning 