

<b>Name: METAL SPLASH cape</b>	<b>Code: MC6118B0</b>	<b>MC61 CLOTHING - NEW METAL SPLASH SERIES</b>
--------------------------------	-----------------------	--

### Description

Cape in 54%  $\text{Ar}$  :  $3 \times 1 \text{ AU}$  20% Wool, 20% Polyamide, 5% Aramid, 1% Antistatic Fibre, 330 g/m<sup>2</sup>, ankle length; with rear Velcro closure, Chinese collar in Flame Retardant fabric and cuffs with inner elastic sleeve.




- Protects during welding operations and aluminium splashes
- Its remarkable properties do not limit the softness and breathability

Suitable to protect the operator from short contacts with the flame, in presence of low values of convective and radiant heat, in welding operations and related processes and from small splashes of molten metal.

The product has been designed and manufactured to comply with Regulation (EU) 2016/425 and subsequent amendments.

CE marked and approved by the Italian Ministry of Labour and Social Security (Ministero del Lavoro e delle Politiche Sociali) as a protective equipment (DPI) for the protection against heat and flame.



Category <b>III</b>	Colours <b>GREY</b>	Available Sizes Made to order: 2S - 3X In stock:
Quantity/Carton <b>20</b>	EC Standards <b>EN 1149-5</b>  <b>EN ISO 11611</b>  Class:2 Values:A1 <b>EN ISO 11612</b>  Limited Flame Spread:A1 Convective Heat:B1 Radiant Heat:C1 Molten Aluminium Splashes:D3 Molten Iron Splashes:E3 Contact Heat:F1	Important Information Aluminium Industry, Foundries, Cement Industry.  Keep in a cool dry place, far from heat sources and direct light. Make sure the garment is in good condition, undamaged and clean before use. Once you become aware of a damage, you should immediately replace it.  We recommend to follow the washing instructions.
Dexterity		Storage and cleaning 