

HELMETS

EVEREST helmet

MD1216E0

FEATURES

High-density polyethylene helmet, designed to ensure protection and resistance even at low temperatures down to -30°C. It also provides protection against falling objects from above and impact resistance. Electrically insulating, safe for live working up to 1000 V AC and 1500 V DC, offering protection against the risk of electric shock. Equipped with side slots for attaching earmuffs, it offers versatility of use in complex work environments. The six-point textile suspension system ensures superior comfort and stability, while the wide textile sweatband keeps the forehead dry. The four-point chin strap with chin cup ensures the correct positioning of the helmet even in dynamic situations. Size adjustment is simple and precise thanks to the ratchet adjustment system, which allows for quick adaptation to the user's needs. Ideal for those seeking safety, comfort, and practicality in extreme conditions.

WEIGHT

465 grams

DETAILS

- Constructed from high-density polyethylene, resistant to low temperatures down to -30°C, featuring a super comfortable six-point textile internal harness that ensures reliable protection even in extreme cold, maintaining comfort and stability through uniform pressure distribution on the head;
- Openings for attaching earmuffs, allowing integration with hearing protection devices, thereby increasing workplace safety;
- Wide textile sweatband, enhancing comfort during prolonged use by keeping the forehead dry;
- Four-point chin strap with chin cup, ensuring correct positioning at all times;
- Ratchet adjustment system for size regulation, allowing for a personalized and quick fit, thereby improving comfort.

SHELF LIFE

3 years from the manufacturing date



AVAILABLE COLOURS

 E0 - YELLOW	 E1 - HI-VIS YELLOW
 H0 - ORANGE	 H1 - HI-VIS ORANGE
 K1 - WHITE	 N0 - LIGHT BLUE

SIZES

ONE SIZE

	In stock
	On production
	Made to order
	Tailor made

FIELDS OF USE

- > CONSTRUCTION - ROAD WORKS
- > PETROCHEMICAL INDUSTRY
- > WORKS AT A HEIGHT

MAINTENANCE

Store in a cool and dry place, away from heat sources and protected from light. Clean all components regularly with a neutral detergent or disinfectant and lukewarm water. Avoid direct contact with alcohol or solvents, which could damage the device.

QUANTITY PER CARTON

20

CATEGORY

III -> This product is currently planned and produced to comply with Regulation (EU) 2016/425 and subsequent modifications.

CERTIFICATIONS AND STANDARDS



PROTECTION FOR INDUSTRY
EN 397



INSULATING PROPERTIES
EN 50365