

## TECHNICAL SHEET

<b>Name: CURRO HELMET</b>	<b>Code: MD1220N0</b>	<b>MD12 SAFETY HELMETS</b>
---------------------------	-----------------------	----------------------------

### Description

ABS helmet with resistance to low temperatures down to -19°C.  
It is an electrically insulating helmet, designed for use in low voltage installations, in live work or in proximity to live parts in installations up to 1000 V in alternating current or 1500 V in direct current. It also offers protection against splashes of molten metals.

Equipped with four-point chinstrap adjustment to always ensure correct positioning and textile 6-point head harness adjustable to two different heights. Size adjustment with ratchet wheel 54-61 cm.  
Weight: 0,396 kg.

The product has been designed and manufactured to comply with Regulation (EU) 2016/425 and subsequent amendments.



Category <b>III</b>	Colours <b>LIGHT BLUE</b>	Available Sizes <b>U</b>
Quantity/Carton  <b>36</b>	EC Standards EN 397  EN 50365	Important Information Store in a cool, dry place, away from heat sources and away from light. Before each use, check that the helmet is in perfect condition, that there are no significant defects on the surface of the shell, such as cracks, splits, deep abrasions, colour changes or dents; if it is not intact, replace it.  Clean all components regularly with neutral detergent or disinfectant and warm water. Avoid direct contact with alcohol or solvents that could damage the device.
Dexterity		Storage and cleaning