

HELMETS

ABS 901 helmet VENTED

MD1224K1

FEATURES

High-strength ABS helmet, designed to ensure protection and maximum comfort during use. It guarantees protection against falling objects from above and impact resistance. It offers reliability, comfort, and safety in high-risk work environments. Equipped with a six-point textile suspension system, it ensures uniform weight distribution and a stable fit. The design includes side slots for earmuff attachment, a chin strap attachment point, and a textile sweatband to keep the forehead dry. Size adjustment is simple and precise thanks to the adjustable and articulated ratchet adjustment system, which allows for quick adaptation to the user's needs. Equipped with ventilation holes that promote air circulation and reduce the sensation of heat during use. Ideal for work environments that require safety, practicality, and prolonged comfort.

WEIGHT

375 grams

DETAILS

- Made of ABS, with a super comfortable six-point textile inner harness, it offers high impact resistance and an even distribution of pressure on the head, ensuring greater safety and comfort even during prolonged use;
- Openings for attaching earmuffs allow integration with hearing protection devices, increasing workplace safety;
- Chin strap attachment ensures a stable fit even during movement or head tilting;
- Adjustable and retractable adjustment wheel for easy size adjustment, allowing for a personalized and quick fit, improving comfort;
- Sweatband increases well-being during prolonged use, keeping the forehead dry;
- Ventilation holes promote air circulation and reduce the sensation of heat during use.

SHELF LIFE

3 years from the manufacturing date



AVAILABLE COLOURS

- | | |
|---|--|
|  E0 - Yellow |  E1 - Hi-vis yellow |
|  H0 - Orange |  K1 - White |
|  L0 - Red |  N0 - Light blue |
|  P0 - Blue | |

SIZES

ONE SIZE

- | | |
|---|---------------|
|  | In stock |
|  | On production |
|  | Made to order |
|  | Tailor made |

FIELDS OF USE

- > Construction - road works
- > Petrochemical industry

MAINTENANCE

Store in a cool and dry place, away from heat sources and protected from light. Clean all components regularly with a neutral detergent or disinfectant and lukewarm water. Avoid direct contact with alcohol or solvents, which could damage the device.

QUANTITY PER CARTON

30

CATEGORY

II -> This product is currently planned and produced to comply with Regulation (EU) 2016/425 and subsequent modifications.

CERTIFICATIONS AND STANDARDS



PROTECTION FOR INDUSTRY
EN 397