

HELMETS

ZEPHYR helmet

MD1225Z9

FEATURES

Protective helmet ideal for those who want maximum protection without sacrificing comfort. It guarantees protection against falling objects from above and impact resistance. Electrically insulating, safe for live working up to 1000 V AC and 1500 V DC, it offers protection against the risk of electric shock. The helmet is certified for use at a temperature down to -30°C. The lateral deformation tests and the + 150°C test were evaluated in accordance with standard EN 397:2012. The polycarbonate-ABS alloy shell makes it lightweight and durable, ensuring safety and practicality. The internal six-point textile harness guarantees a stable and comfortable fit even during prolonged use. It is equipped with openings for attaching earmuffs, a four-point adjustable chinstrap with chin cup, a textile sweatband, and a ratchet adjustment wheel for quick and precise size adjustment. Furthermore, the quick-release mechanism allows attaching and detaching the visor with extreme ease in any situation. Circumference: 52-63 cm

WEIGHT

475 grams

DETAILS

- Polycarbonate-ABS alloy shell, with internal six-point textile harness, combines strength and lightness for reliable protection, while the six-point harness distributes pressure evenly, ensuring comfort even during prolonged use;
- Integrated lamp clip in the shell, for headlamp attachment;
- Openings for attaching earmuffs, allows integration with hearing protection devices, increasing workplace safety;
- Four-point chin strap with chin cup, to always ensure correct positioning (also available as spare part MD1545);
- Textile sweatband, increases comfort during prolonged use, keeping the forehead dry (also available as spare part MD1544);
- Rear adjustment wheel, ensures a perfect fit and allows for quick and personalized adjustment, improving comfort.
- Quick release mechanism for visor removal, allows for quick operation by pressing the dedicated buttons.



SHELF LIFE

5 years from the date of manufacture

AVAILABLE COLOURS

- | | |
|---|--|
|  E0 - YELLOW |  E1 - HI-VIS YELLOW |
|  H0 - ORANGE |  K1 - WHITE |
|  L0 - RED |  N0 - LIGHT BLUE |
|  P8 - ROYAL |  R3 - LIME GREEN |
|  Z9 - BLACK | |

SIZES

ONE SIZE

- | | |
|---|---------------|
|  | In stock |
|  | On production |
|  | Made to order |
|  | Tailor made |

FIELDS OF USE

- > CONSTRUCTION - ROAD WORKS
- > PETROCHEMICAL INDUSTRY

MAINTENANCE

Store in a cool and dry place, away from heat sources and protected from light. Clean all components regularly with a neutral detergent or disinfectant and lukewarm water. Avoid direct contact with alcohol or solvents, which could damage the device.

QUANTITY PER CARTON

12

CATEGORY

III -> This product is currently planned and produced to comply with Regulation (EU) 2016/425 and subsequent modifications.

CERTIFICATIONS AND STANDARDS



PROTECTION FOR INDUSTRY
EN 397



INSULATING PROPERTIES
EN 50365
Class: 0