



VAT Nr. IT 03359340548
Viale Europa 74
20090 Cusago Milano
Tel. +39 02.90394575
Fax +39 02.90394441

export@sirsafety.com
www.sirsafety.com



UNI EN ISO 9001:2015
UNI EN ISO 14001:2015
UNI EN ISO 45001:2018

Name: V-GARD 500 helmet	Code: MD1414H0	MD14 MSA HELMETS
--------------------------------	-----------------------	-------------------------

High quality helmet with ABS shell with Push-Key 4-point head harness and textile straps with ratchet wheel adjustment, for increased stability. Incorporated slots for hearing and face protection. Available in vented (for which electrical insulation is not effective) and non-vented shell. Size adjustment between 52-62 cm. Weight: 340 g.

A^{\wedge} \tilde{A} [\tilde{A} { } ^{\wedge}] ^{\wedge} a e [^{\wedge} \tilde{A} H E C);
 Sae^{\wedge} a q^{\wedge} [] { aq } A SOL
 A)^{\wedge} & d 3 a q^{\wedge} • [aq] A 40V AC);
 A)^{\wedge} & d 3 a q^{\wedge} • [aq] A q [] çakOP / 50365 electric shock up to 1000 V AC
 or 1500 V DC;
 AE a caa2Ae [] [çakOP A DU 80079-36 for zone 1, 2 Group IIA and for
 zone 20, 21, 22 Group IIIA, IIIB, IIIC.

The product has been designed and manufactured to comply with Regulation(EU) 2016/425 and subsequent amendments



Category III	Colours ORANGE	Available Sizes Made to order: U In stock:
Quantity/Carton 20	EC Standards EN 397 EN 50365	Important Information Safety helmet suitable to protect the workers' head from objects falling from a height or accidental impacts in industrial plants. The ABS shell ensures a high impact and chemical resistance, thus making the helmet a perfect protection device in chemical and petrochemical industry. Make sure the helmet is in good condition before use and its shell is not damaged: inspect for cracking, abrasions, change of colouring or dents. Once you become aware of a damage, you should immediately replace it. Keep in a cool dry place, far from heat sources and direct light. Clean using only a neutral detergent and warm water. Do not use any solvents.
Dexterity		Storage and cleaning